
Grease Fitting 1 of 4



1/8" PTF Fittings				
Part Number	Style	Hex	Overall	Shank
1644	Straight	7/16	9/16	15/64
1610	Straight	7/16	11/16	19/64
1607	Straight	7/16	1-1/4	25/32
1669	Straight	7/16	1-3/4	1-17/64
1684	Straight	3/8	2-5/8	2-3/16
1618	Straight	1/2	1	9/32
1958	Straight	7/16	31/32	1/4
1611	30	7/16	29/32	19/64
1638	30	7/16	2-3/32	1-1/4
1688	45	7/16	57/64	
1620	45	7/16	1-1/8	
1612	65	7/16	27/32	
1623	65	7/16	1-7/32	
1649	65	3/8	2-3/4	
1613	90	7/16	27/32	
1606	90	7/16	1- 13/16	
369599	Straight	7/16	2-5/8	
369608	65	7/16	29/32	
36957	Double 70	1/2	27/32	

Alemite 1/8" PTF Fittings are used on industrial machines and heavy equipment

1/4-28" and 1/8" Thread Forming Fittings			
Part Number	Style	Hex	Hole Size (recommended)
3038	Straight	5/16	.230235
3053	45	3/8	.230235
3054	90	3/8	.230235
1720	Straight	7/16	.373380
1723	90	7/16	.373380
1724	45	7/16	.373380
369582	Straight	9/32	.230235

Alemite Thread Forming Fittings have special tapered drive threads which reshape the material in an untapped hole to provide a leak proof seal. They are most

effectively installed by spinning into the untapped hole, but may be driven straight into the untapped hole. Thread forming fittings can be replaced by any standard threaded fitting or by another thread forming fitting.

1/4-28" Taper Thread Fittings				
Part Number	Style	Hex	Overall	Shank
1641	Straight	5/16	35/64	3/16
1652	Straight	5/16	11/16	23/64
1680	Straight	5/16	31/32	5/8
1698	Straight	5/16	1-1/8	25/32
3014	Straight	5/16	1-5/8	1
1637	45°	3/8	13/16	13/64
3010	65°	3/8	25/32	19/64
1911	90°	3/8	3/4	13/64

Alemite 1/4"-28 Taper Thread Fittings are used on most cars and trucks, as well as many industrial machines. It is recommended that SAE-LT taper threads be assembled into 1/4"-28 UNF, Class 3B, straight threaded holes

having a modified maximum minor diameter of 0.2151", to ensure 75% minimum thread height

1/4-28"	PTF	Fittings
---------	-----	----------

Part Number	Style	Hex	Overall	Shank
1627	Straight	9/16	7/8	27/64
1629	67.5	9/16	31/32	11/32

Alemite 1/4" PTF Fittings are widely used for larger bearings on farm machinery and heavy industrial equipment. Recommended for heavy lubricants in cold weather.