

Poly Nut

Steel Poly Nut Zinc: NRIV020----X---Z1

Aluminum Poly Nut: NPOLALM----X---

Note: Smaller Head Flange than Rivet Nut for nearly flush application

Thread Size	Steel Marson #	Aluminum Marson #	D	B	A	Grip Range		Hole Size		Drill Size
			Body Dia.	Head Dia.	Body Length	Min	Max	Min	Max	
6-32	57415	57510	.249	.287	.410	.020	.080	.250	.254	1/4"
8-32	57425	57520	.249	.287	.410	.020	.080	.250	.254	1/4"
10-24	57435	57530	.280	.320	.465	.020	.130	.281	.285	9/32"
10-32	57445	57540	.280	.320	.465	.020	.130	.281	.285	9/32"
1/4-20	57455	57550	.374	.415	.610	.030	.165	.375	.379	3/8"
5/16-18	57475	57575	.499	.540	.720	.030	.165	.500	.504	1/2"
3/8-16	57485	57585	.499	.540	.720	.030	.165	.500	.504	1/2"
4mm	57407	.	.249	.287	.410	.020	.080	.250	.254	1/4"
5mm	57409	.	.280	.320	.465	.020	.130	.281	.285	9/32"
6mm	57411	.	.374	.415	.610	.030	.165	.375	.379	3/8"
8mm	57413	.	.499	.540	.720	.030	.165	.500	.504	1/2"
10mm	57414	.	.499	.540	.720	.030	.165	.500	.504	1/2"