

Thread-Sert



Before set



Completed application

Steel Thread-Sert Zinc: NTHR020----Z1

Note: For almost Flush Installations

Thread Size	Material Thickness		Material Thickness		Delta Part Number	Marson Part #
	.0937 - .1562		.0937 - infinity			
	Hole Size	Drill Size	Hole Size	Drill Size		
4-40					0040Z1	
6-32	.221	# 2	.234	A	0060Z1	47810
8-32	.250	1/4"	.261	G	0080Z1	47820
10-24	.281	9/32"	.290	L	0100Z1	47830
10-32	.281	9/32"	.290	L	0101Z1	47840
1/4-20	.391	25/64"	.391	25/64"	0250Z1	47850
5/16-18	.500	1/2"	.516	33/64"	0310Z1	45871
3/8-16	.562	9/16"	.578	37/64"	0370Z1	47881

Aluminum Thread-Sert Zinc: NTHRALM----

Note: For almost Flush Installations

Thread Size	Material Thickness		Material Thickness		Delta Part Number	Marson Part #
	.0937 - .1562		.0937 - infinity			
	Hole Size	Drill Size	Hole Size	Drill Size		
6-32	.221	# 2	.234	A	0060	47910
8-32	.250	1/4"	.261	G	0080	47920
10-24	.281	9/32"	.290	L	0100	47930
10-32	.281	9/32"	.290	L	0101	47940
1/4-20	.391	25/64"	.391	25/64"	0250	47950
5/16-18	.500	1/2"	.516	33/64"	0310	47971
3/8-16	.562	9/16"	.578	37/64"	0370	47981