
Socket Pipe Plugs 3/4 Taper

(Dimensions are for reference ONLY!)
(There are many different plug standards, Short, Long and can vary by Material)

Socket Pipe Plug 3/4 Taper

Dry Seal
Both can be referred to as "Dry Seal"
Carbon Steel = PPS020---Alloy Steel (38 HRC) = PPS800---Stainless Steel = PPS188---Stainless Steel = PPS316---Nylon = PPSNYL----



	0		S	K	W	L Overall Length	
Nominal Size	Nominal O.D.	Threads Per Inch	Hex Socket	Key Engage- ment	Wall Thickness		
			Size	Min	Min	Max	Max
1/16	0.315	27	5/32	.140	.062	.324	.300
1/8	0.408	27	3/16	.140	.062	.324	.300
1/4	0.542	18	1/4	.218	.073	.457	.417
3/8	0.681	18	5/16	.250	.084	.520	.480
1/2	0.844	14	3/8	.312	.095	.582	.542
3/4	1.057	14	9/16	.312	.125	.645	.605
1	1.322	11-1/2	5/8	.375	.125	.770	.730
1-1/4	1.669	11-1/2	3/4	.437	.156	.832	.792
1-1/2	1.908	11-1/2	1	.437	.156	.843	.780
2	2.385	11-1/2	1	.437	.156	.906	.844
2-1/2	2.872	8	1	.500	.250	1.080	1.050
3	3.497	8	1	.500	.250	1.140	1.100
3-1/2	3.997	8	1	.500	.250	1.200	1.160
4	4.498	8	1	.500	.250	1.270	1.230

Note: "3/4 Taper" and "7/8 Taper" fit into the same hole. The "3/4 Taper" will stick up out of the hole a bit, the "7/8 Taper will be Flush.

Note: Both "3/4 Taper" and "7/8 Taper" can be referred to as "Dry Seal".

Actual Outside Diameters of Pipe Thread											
(Dimensions are same for all types of plugs)											
1/8-27	1/4-18	3/8-18 1/2-14		3/4-14	1-11 1/2						